PP4-10

COLUMNAR MINI ARRAY SYSTEM

±5 dB 120 Hz ~ 18 KHz



- 10 X 4" Full Range Neodymium Driver
- High Quality System for Musicians for Live Music
- Low Distortion, Maximum Intelligibility
- Museum & Exhibition especially for Reverberate Halls
- Custom Color Available
- Flexible Mounting Options for Easy Installation Included
- Powering Mode: Full-Range Passive
- For Portable or Permanent Installation

Product Information

PP4-10 is ideal for live music. The cabinet with comprehensive hardware permits easy installation. PP4-10 is ideal for sound reinforcement in A/V events, paging and background music. The small dimensions of system permit the portable use. PP4-10 uses 10 full-range speakers of 100 mm (4") with Neodymium magnet and 25 mm (1") voice coil weather-resistant cone. The total nominal impedance is 6 $\Omega.$ The cabinet is sealed enclosure of Birch Plywood of 14 mm and 6 mm curvedon side. Despite the ultra-low size PP4-10 surprises in the natural timbre sound.

Data Sheet

Frequency Response

	-10 dB 100 Hz
Sensitivity (1 Watt @ 1 m) Max SPL Calculated	99.5 dB 126 dB
Nominal Input Impedance (Ω)	6 Ω
Power Handling (Watts Cont. AES) Peak Power	500 W 2000 W
Nominal Dispersion (@ -6 dB)	80° (H) x 20° (V)
Dimensions mm (±1 mm) (H x W x D)	1.130 x 125 x 144
Weight	9.5 Kg

Enclosure Material

- Enclosure Material: Birch Plywood of 14 mm and 6 mm on Side
- Finish: Texture Polyurethane Black Paint
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: 1 Neutrik NL4 Speakon
- Optional Accessories: Speaker Bag, Wall-Mount & Pole-Mount Hardware

INSTALL | EVENTS | PORTABLE

