

PULCEW

COMPACT STEREO SUBWOOFER SYSTEM



- Dual 6" LF in Band Pass Vented Enclosure
- Powering Mode: LF Passive
- For Permanent Installation

Product Information


PULCEW is a stereo subwoofer with high output low distortion that provides response in the range 40 - 180 Hz. PULCEW uses dual 160 mm (6") low frequency cone with 38 mm (1.5") voice coil for better performance in permanently installed applications. PULCEW offers passive powering mode, band-pass mechanical filter and the internal crossover network for satellite out. PULCEW performs well with PULCE loudspeakers to form full-range reproduction systems, it is also compatible with other LSS small mid-range loudspeaker. On request can be ordered passive crossover network with system of EQ for satellites.

Data Sheet

Frequency Response	±5 dB 40 Hz ~ 180 Hz -10 dB 30 Hz
Sensitivity (1 Watt @ 1 m) Max SPL Calculated	92 dB 114 dB
Nominal Input Impedance (Ω)	8+8 Ω
Power Handling (Watts Cont. AES)	80+80 W
Nominal Dispersion (@ -6 dB)	360°
Dimensions mm (±1 mm) (H x W x D)	270 x 400 x 400
Weight	10,4 Kg

Enclosure Material

- Enclosure Material: MDF of 12 mm
- Finish: Texture Polyurethane Black Paint
- Connectors: Black and Red Clamps or 2 Neutrik NL4 Speakon



INSTALL | EVENTS | PORTABLE